COLORPRINT NEW

Description
Very thin heat seal material, specifically formulated for ink jet solvent and eco solvent based inks – printing and cutting systems.
Paper backing.

Basic Information
Due to the many different base materials available on the market, the following heat transfer instructions are given as guideline only:
Temperature: 160-165°C
Time: 15"
Pressure: medium

Application Instructions
1) Print the material and wait at least 3 minutes before cutting (the dry time is normally settable in automatic mode)
2) Cut the material
3) Let the print dry at least 12 hours before rolling, overlaying or heat transferring the material
4) Weed the exceeding material
5) Remove the image from the backing using the **Siser T.T.D. Advanced** (adhesive, transparent polyester, resistant to high temperatures)
6) Heat apply
7) Remove application tape **hot.** Should you use other application tapes, follow the manufacturer's instructions

Suitable for
Cotton, polyester, poly-cotton blends.
Not suitable for treated and dyed garments (sublimation inks)

Washing: (wait 24h after the heat transfer)
50°C Max. – wash inside out - do not use bleach or other aggressive chemical agents
Dry-cleaning : no
Tumble drier : not advisable

N.B. : all information given in this sheet are based on our experience
We recommend to always perform a test before starting standard production

The product meets the Italian and Ue regulations relating to its proper use.
This document can be subject to variations. Updated versions are available on our website www.siser.it.
For further information, please contact our Sales Office. Thank you.

SISER s.r.l.
V.LE DELLA TECNICA n. 18 – 36100 VICENZA ITALY
TEL. +39 0444 287960 - FAX +39 0444 287959 - E-mail: info@siser.it - www.siser.it
R.E.A. VI 171856 VI – Reg. Imp. VI n. 14971 - Cap. Soc. € 103.300 i.v. – Partita IVA 01591490246