

## P.S. METALLIC

### Description

Heat seal material, with metallic surface, for Cad-Cut® applications.

Not fit for multi-layered applications.

**Adhesive polyester backing.**

### Basic Information

Due to the many different base materials available on the market, the following heat transfer instructions are given as guideline only:

**Temperature:** 160° C

**Time:** 15”

**Pressure:** medium

### Application Instructions

- 1) Cut the material **in reverse**
- 2) Weed the exceeding material (for an easier weeding, we suggest to leave the cut material on a hot surface – 60/70°C – for a few seconds)
- 3) Place the material on the garment with its polyester support
- 4) Heat apply
- 5) Wait 3-5 seconds and remove polyester backing

### Suitable for

Cotton, polyester, poly-cotton blends.

Not suitable for treated and dyed garments (sublimation inks)

### Washing: (wait 24h after the heat transfer)

Possibly, hand wash in cold water – inside out - do not use bleach or other aggressive chemical agents

**Dry-cleaning :** no

**Tumble drier :** no

*N.B. : all information given in this sheet are based on our experience*

**We recommend to always perform a test before starting standard production**

The product meets the Italian and Ue regulations relating to its proper use.

This document can be subject to variations. Updated versions are available on our website [www.siser.it](http://www.siser.it).

For further information, please contact our Sales Office. Thank you.

### SISER s.r.l.

V.LE DELLA TECNICA n. 18 – 36100 VICENZA ITALY

TEL. +39 0444 287960 - FAX +39 0444 287959 - E-mail: [info@siser.it](mailto:info@siser.it) - [www.siser.it](http://www.siser.it)

R.E.A. VI 171856 VI – Reg. Imp. VI n. 14971 - Cap. Soc. € 103.300 i.v. – Partita IVA 01591490246

